



Feature

- Transmit HDMI signals over Cat5e or above cable
- Supports 1080P pixels HDMI signal transmission and transmission distance can reach up to 25 meters
- Plug and play, no need extra power
- High quality and performances
- Built in TVS for ESD and surge protection

Note: It is a passive HDMI balun, so transmission distance is related with the driving capability of HDMI player.

Installation

- Please use the HDMI TX balun to plug into the interface of HDMI player
- Please use the HDMI RX balun to plug into the HDMI interface of LCD/OLED display
- Use a cat5e cable to connect HDMI TX balun with HDMI RX balun
- Make sure all the connections are right and the video will come within ten seconds

Caution

- It is HDMI extender, so signal transmission is very fast, please make sure the Cat5e cable is pure copper, not CCA!
- The device is not waterproof and not to be used outdoors
- Clean only with dry cloth
- Do not install near any heat sources such as radiators, heatregisters, stoves, or other apparatus that produce heat
- Refer all servicing to qualified service personnel

OLC-HDP2000 Made in China

C: 0 M: 31 Y: 100 K: 0
PANTONE: 7406 C

C: 0 M: 100 Y: 100 K: 0
PANTONE: 485 C

OLC-HDP2000

尺寸：70*63mm，材质：双面铜版纸250克